VENDOR COMPLIANCY FORM

Please mark if required specifications are met by checking the appropriate line
Exceptions noted shall include documentation as requested in the quote
Compliancy form shall be submitted electronically to Brian Boehs, Senior Contracting Officer at bboehs@lakecountyfl.gov

Rubber Tire Skid Steer with High Flow Hydraulics, 24" Cold Planner and Pallet Forks

	Compliant		
1.0 GENERAL:			
1.01 Wheel Base Minimum 48"	Y _____	N _____	Exception ___
1.02 Bucket Pin Height at max lift 122"	Y _____	N _____	Exception ___
1.03 Ground clearance minimum 8"	Y _____	N _____	Exception ___
1.04 Vehicle width minimum 65"/Maximum 84"	Y _____	N _____	Exception ___
1.05 Rubber tire only (no tracks)	Y _____	N _____	Exception ___
1.06 Joy Stick controls in cab	Y _____	N _____	Exception ___
1.07 Minimum 66" Low Profile Bucket	Y _____	N _____	Exception ___
1.08 Pallet Forks	Y _____	N _____	Exception ___
1.09 Manual Attachment Coupler	Y _____	N _____	Exception ___
2.0 ENGINE:			
2.01 Diesel Engine current EPA requirements	Y _____	N _____	Exception ___
2.02 Gross horsepower minimum - 70	Y _____	N _____	Exception ___
2.03 Engine Displacement – 200 cubic inches	Y _____	N _____	Exception ___
3.0 HYDRAULIC SYSTEM:			
3.01 Hydraulic Flow Std. 23 gal/min	Y _____	N _____	Exception ___
3.02 High Flow Hydraulic 32 gal/min	Y _____	N _____	Exception ___
3.03 Hydraulic Power 40HP	Y _____	N _____	Exception ___
3.04 Hydraulic Pressure minimum 3300 psi	Y _____	N _____	Exception ___
4.0 POWER TRAIN:			
4.01 Forward Travel Speed 7 mph	Y _____	N _____	Exception ___
4.02 Reverse Travel Speed 7 mph	Y _____	N _____	Exception ___
4.03 Forward Travel Speed 2 speed opt. 10 mph	Y _____	N _____	Exception ___
4.04 Reverse Travel Speed 2 speed opt. 10 mph	Y _____	N _____	Exception ___
5.0 CAB:			
5.01 Enclosed Cab with Factory Installed Air Conditioning and Heat	Y _____	N _____	Exception ___
5.02 Hand and Foot Throttle Control	Y _____	N _____	Exception ___
5.03 Interior Rear View Mirror	Y _____	N _____	Exception ___
5.04 Suspension or Air Ride Vinyl Seat with Arm Rests	Y _____	N _____	Exception ___
5.05 12 Volt Power Supply	Y _____	N _____	Exception ___
6.0 OPERATING CAPACITIES:			
6.01 Rated Operating Capacity 2100 lb.	Y _____	N _____	Exception ___
6.02 Tip Load 4100 lb.	Y _____	N _____	Exception ___
7.0 FINAL DELIVERY:			
7.01 Delivery of Complete Unit – FOB Fleet Garage	Y _____	N _____	Exception ___
8.0 SERVICE MANUALS AND TRAINING:			
8.01 Provide Complete Literature and Specifications	Y _____	N _____	Exception ___
8.02 Provide User Training	Y _____	N _____	Exception ___
8.03 Provide two (2) complete parts/service manuals.	Y _____	N _____	Exception ___
8.04 Provide two (2) complete operator's manuals	Y _____	N _____	Exception ___
8.05 Provide two (2) sets of keys	Y _____	N _____	Exception ___

9.0 24" COLD PLANER ATTACHMENT DRUM:

9.01 Drum width 24" Y _____ N _____ Exception ___
9.02 Drum Torque Minimum 800 ft-lb Y _____ N _____ Exception ___
9.03 Number of Bits Minimum 50 Y _____ N _____ Exception ___
9.04 Drum Speed Minimum 180 rpm Y _____ N _____ Exception ___

10.0 24" COLD PLANER ATTACHMENT HYDRAULICS:

10.01 Hydraulic Flow Range 23 – 40 gal/min Y _____ N _____ Exception ___
10.02 Hydraulic Angle Tilt 8.5 degrees minimum Y _____ N _____ Exception ___
10.03 Hydraulic Depth Control minimum 6" Y _____ N _____ Exception ___
10.04 Hydraulic Side Shift Control Y _____ N _____ Exception ___

11.0 WARRANTY:

11.01Manufacturer's standard warranty Y _____ N _____ Exception ___
11.02 State Period of warranty _____

_____
Vendor Name

_____ _____
Vendor's Authorized Signature Date